

Sample of Recommended Specification

A blank downloadable Recommended Specification form is available at dalsouple.com

1 The floor covering is Dalsouple rubber flooring

2 The Dalsouple product range is _____ eg DalMicro

3 The production type is Standard DalNaturel*

* Please check if your choice is available in DalNaturel.

4 The surface finish is _____ eg Martelé

5 The tile/roll size is _____ eg 1760 x 680mm

6 The thickness is _____ eg 2.5mm

Dalsouple recommends a minimum thickness of 2.5mm for floors

7 The colour is _____ eg Vert Ecosais

8 DalTerrazzo Base colour _____ eg Bleu Pâle

Chip colour _____ eg Vanille

Density _____ eg Medium

Chip shape(s) _____ eg Mini Triangles

9 DalMarbre Base colour _____ eg Pistache

Marbre colour(s) & Percentage(s) _____ eg Banane 50%

10 The price per square metre is _____

- **Installation** shall be in strict accordance with BS8203 approved methods, or local equivalent. Tiles should be laid broken-bonded in most cases. Please refer to us for exceptions to this. Back of each tile should be brushed prior to installation. Plaques should be back rolled prior to installation. Installation shall be carried out by an experienced installer: contact Dalsouple 01278 727777 for a current listing of flooring contractors with experience of Dalsouple flooring. Installation shall be deferred until all other work that might cause damage to the flooring is completed and the floor must be protected after installation.
- **Surface Preparation and Adhesives** please contact Tremco Technical Service tel 01753 691696 or Mapei (UK) Technical Service tel 0121 508 6970
- **Cleaning and maintenance** shall be in accordance with the Dalsouple Total Floor Care Guide tel 01278 671185
- **Accessories** please contact Gradus Ltd. tel 01625 428922

The companies listed within this guide are all independent and Dalsouple are not responsible for the quality of service, or the products, which they provide.