



DALSOUPLE

Recommended Specification

- 1 The floor covering is Dalsouple rubber flooring
- 2 The Dalsouple product range is _____
- 3 The production type is Standard DalNaturel*
* Please check if your choice is available in DalNaturel.
- 4 The surface finish is _____
- 5 The tile size is _____
- 6 The tile thickness is _____
Dalsouple recommends a minimum thickness of 2.5mm for floors
- 7 The colour is _____
- 8 **DalTerrazzo** Base colour _____
 Chip colour _____
 Density _____
 Chip shape(s) _____
- 9 **DalMarbre** Base colour _____
 Marbre colour(s) & Percentage(s) _____
- 10 The price per square metre is _____

- **Installation** shall be in strict accordance with BS8203 approved methods, or local equivalent. Tiles should be laid broken-bonded in all cases. Back of each tile should be brushed prior to installation. Plaques should be back rolled prior to installation. Installation shall be carried out by an experienced installer: contact Dalsouple 01278 727777 for a current listing of flooring contractors with experience of Dalsouple flooring. Installation shall be deferred until all other work that might cause damage to the flooring is completed and the floor must be protected after installation.
- **Surface Preparation and Adhesives** please contact
Tremco Technical Service tel 01753 691696 or
Mapei (UK) Technical Service tel 0121 508 6970
- **Cleaning and maintenance** shall be in accordance with
the Dalsouple Total Floor Care Guide tel 01278 652150
- **Accessories** please contact
Gradus Ltd. tel 01625 428922

If you have any queries regarding this specification form please contact us.

Dalsouple, Showground Road, Bridgwater, Somerset, TA6 6AJ, England.
tel +44(0)1278 727777 fax +44(0)1278 727788 email info@dalsouple.com web www.dalsouple.com